## **AMENDMENTS TO THE CLAIMS**

Docket No.: 3449-0274P

1. (Currently Amended) A bi-directional remote controller comprising:

means for requesting a guidance on a data broadcasting;

means for receiving guidance information provided from an outside in response to the request; and

means for notifying the received guidance information,

wherein the guidance information is extracted while from the data broadcasting is displayed and wherein the guidance information is used for a user to operate at least one function being included in the data broadcasting.

2. (Original) The bi-directional remote controller according to claim 1, wherein the requesting means is a guidance setting button key.

## 3. (Cancelled)

- 4. (Original) The bi-directional remote controller according to claim 1, wherein the guidance information indicates the location of a button key to be pushed.
- 5. (Original) The bi-directional remote controller according to claim 1, wherein the guidance information indicates the location of a button key allowed to be pushed.
- 6. (Original) The bi-directional remote controller according to claim 1, further comprising means for inputting a response instruction on the guidance information.
- 7. (Original) The bi-directional remote controller according to claim 6, wherein the inputting means is a button key provided on a portion notified by the notifying means.

Reply to Office Action of April 19, 2006

8. (Original) The bi-directional remote controller according to claim 6, wherein the

Docket No.: 3449-0274P

inputting means is a plurality of button keys provided on a portion notified by the notifying

means.

9. (Original) The bi-directional remote controller according to claim 1, wherein the

notifying means is a display device.

10. (Original) The bi-directional remote controller according to claim 1, wherein the

notifying means is provided at a predetermined portion of the inputting means.

11. (Currently Amended) A data broadcasting guidance system comprising:

means for extracting guidance information while from a data broadcasting is displayed;

means for requesting a guidance on the data broadcasting; and

means for notifying the extracted guidance information in response to the request from

the requesting means, wherein the guidance information is used for a user to operate at least one

function being included in the data broadcasting.

12. (Original) The data broadcasting guidance system according to claim 11, further

comprising means for displaying the extracted guidance information in response to the request

from the requesting means.

13. (Original) The data broadcasting guidance system according to claim 11, further

comprising means for receiving the extracted guidance information in response to the request

from the requesting means.

14. (Original) The data broadcasting guidance system according to claim 11, further

comprising means for inputting a response instruction on the guidance information provided

through the notifying means.

3 EHC/sld Reply to Office Action of April 19, 2006

15. (Previously presented) The data broadcasting guidance system according to claim 14,

wherein the inputting means is a button key provided on a portion notified by the notifying

means.

16. (Previously presented) The data broadcasting guidance system according to claim 14,

wherein the inputting means is a plurality of button keys provided on a portion notified by the

notifying means.

17. (Original) The data broadcasting guidance system according to claim 11, wherein the

requesting means is a guidance setting button key.

18. (Previously presented) The data broadcasting guidance system according to claim 11,

wherein the guidance information indicates the location of a button key to be pushed or allowed

to be pushed.

19. (Previously presented) The data broadcasting guidance system according to claim 11,

wherein the requesting means and the notifying means are provided at a remote controller, and

the extracting means is provided at a data broadcasting display device remotely controllable by

the remote controller.

20. (Original) The data broadcasting guidance system according to claim 11, wherein the

notifying means is a display device.

21. (Original) The data broadcasting guidance system according to claim 11, wherein the

notifying means is provided at a predetermined portion of the inputting means.

22. (Currently Amended) A method for guiding a data broadcasting, the method

comprising the steps of:

4 EHC/sld

Docket No.: 3449-0274P

Application No. 10/667,610 Amendment dated July 19, 2006

Reply to Office Action of April 19, 2006

(a) extracting guidance information while from the data broadcasting is displayed;

(b) requesting a guidance on the data broadcasting; and

(c) notifying the extracted guidance information in response to the request,

wherein the guidance information is used for a user to operate at least one function being

Docket No.: 3449-0274P

included in the data broadcasting.

23. (Original) The method according to claim 22, further comprising the step of (d)

displaying the guidance information.

24. (Original) The method according to claim 22, further comprising the step of (e)

receiving the guidance information.

25. (Original) The method according to claim 22, further comprising the steps of:

(f) inputting a response instruction on the guidance information; and

(g) performing a navigation according to the inputted response instruction.

26. (Original) The method according to claim 22, wherein the request is performed by

pushing a guidance setting button key.

27. (Previously presented) The method according to claim 22, wherein the guidance

information indicates the location of a button key to be pushed or allowed to be pushed.

28. (Previously presented) The method according to claim 22, wherein in the step (a),

the guidance information is extracted by a data broadcasting display device while the data

broadcasting is displayed on the data broadcasting display device; and in the step (c), the

extracted guidance information is notified on a remote controller used to remotely control the

data broadcasting display device.

5 EHC/sld

Docket No.: 3449-0274P

29. (New) The bi-directional remote controller according to claim 1, wherein the guidance information indicates at least one of input parts to be inputted in order for the user to input a command corresponding to at least one of the at least one function being included in the data broadcasting.

## 30. (New) A method comprising:

- (a) receiving a digital broadcasting signal including audio and/or video signal and a data broadcasting signal, wherein the data broadcasting signal for data broadcasting comprises guidance information and data broadcasting data based on Java language;
  - (b) extracting the guidance information from the data broadcasting signal; and
- (c) providing the extracted guidance information based on a request for a guidance on the data broadcasting, wherein the guidance information is used for a user to operate at least one function being included in the data broadcasting.

6 EHC/sld